



ENOCHS ENCORE

LOW ACCESS

compare.

	ENCORE 4550 Programmable Low Access Table	ENCORE 4520 Low Access Table	ENCORE 4510 Basic Low Access Table
Warranty:	4-YEAR	4-YEAR	2-YEAR
Operation:	Programmable with 3 memory positions	Non-programmable	Non-programmable
Patient Load:	700 Lbs.		
Power Adjustments:	Height: Low-Access: 18.5" to 38" maximum Back: Horizontal to 80°		
Controls:	Hand Control, Programmable	Foot Control	Foot Control
Couch Top:	100% seamless vacuum formed style, all steel frame construction		
Perineal Recess:	Moulded, no seams, 10" W x 2" D at center point		
Pelvic Tilt:	11°		
Leg Extension:	Extends out 20" from end of seat section		
Irrigation Basin:	Stainless Steel, 2.5" deep		
Master ON/OFF Switch:	Shuts off power to entire product		
Stirrups:	Multi-positional, lateral, and length adjustment		
Storage:	Side Drawer: Field reversible, 15.5" W x 15" D x 4" H	No side drawer	
	Footend Drawer: stainless steel, 16" W x 10.75" D x 4" H		
Base Construction:	Fully welded all steel base		
Paper Roll Holder:	Accommodates 18" or 21" table paper widths		
Accessories:	Grab rails, knee crutches, padded armboard, drawer locks, restraint straps, IV pole, urology basin with screen and drain, headend accessory rails, foot end rails		
Power System:	Electro-mechanical operating system		
Mains Power Entry:	IEC connection with internal circuit breaker, detachable cord		
Table Duty Cycle:	1 minute run/9 minutes rest		
Table Rating:	115V 60Hz 10 amps		
Table Dimensions:	Width: 27", Height: 18.5" - 38", Length: 52" (extends to 72")		
Certifications:	Classified by UL to ANSI/AAMI ES60601-1 (2005) + AMD 1 (2012), CAN/CSA-C22.2 No. 60601-1 (2014)		

	ENCORE 4550 Add-On Options			ENCORE 4520 Add-On Options			ENCORE 4510 Add-On Options	
	Electrical Receptacles*	Instrument Warmer**	Foot Control	Electrical Receptacles*	Instrument Warmer**	Hand Control: non-programmable	No Add-On Options	
-01	•	•		-01	•	•		
-02	•			-02	•			
-03		•		-03		•		
-04	•	•	•	-04	•	•	•	
-05		•	•	-05		•	•	
-06	•		•	-06	•		•	
-07			•	-07		•	•	

* Hospital grade, dual receptacles with easy access dedicated circuit breaker
Duty Cycle: Continuous operation
Total Load: 3.9 amps Rating: 115V 60Hz

** 45 Watts, ON/OFF switch with integrated circuit breaker
Duty Cycle: Continuous operation